

## LEDTOUCH Skyline Recessed

Indoor LED batten luminaires



### Areas of application

- Offices
- Hospitals
- Banks
- Service centers
- Schools
- For indoor use only

### Product benefits

- Elegant design
- Robust structure and cutting-edge optics
- Consistent white light, SDCM (Standard Deviation of Color Matching): < 3.5
- No deformation thanks to advanced housing design

### Product features

- Available with on/off switch or DALI dimmer (1...100 %)
- Long lifetime: up to 50,000 h
- Simple and rapid installation
- Reduce installation costs thanks to flexible structure
- Flexible installation (line, L or square shape)
- LIGHTIFY Pro smart wireless control
- High luminaire efficacy: up to 117 lm/W



## Product family datasheet

### Technical data

Product description	Electrical data			Photometrical data		Light technical data		Dimensions & weight		
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Color rendering index Ra	Beam angle	Light distribution	Length	Width	Height
LEDTOUCH Skyline Recessed 600 mm 840	18 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	624.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 600 mm 865	18 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	624.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 1200 mm 840	35 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	1224 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 1200 mm 865	35 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	1224 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed Corner 840	21 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	411.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed Corner 865	21 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	411.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 1200 mm 840 DALI	35 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	1224 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 1200 mm 865 DALI	35 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	1224 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 600 mm 840 DALI	18 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	624.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed 600 mm 865 DALI	18 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	624.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed Corner 840 DALI	50 W	220...240 V	50/60 Hz	4000 K	>80	110 °	symmetric	411.0 mm	116.0 mm	66.0 mm
LEDTOUCH Skyline Recessed Corner 865 DALI	21 W	220...240 V	50/60 Hz	6500 K	>80	110 °	symmetric	411.0 mm	116.0 mm	66.0 mm

## Product family datasheet

Product description	Colors & materials			Temperatures & operating conditions	Capabilities	Certificates & standards		Country specific categorizations
	Body material	Product color	Cover material	Ambient temperature range	Type of installation	Protection class	Type of protection	Order reference
LEDTOUCH Skyline Recessed 600 mm 840	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 600 mm 865	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 1200 mm 840	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 1200 mm 865	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed Corner 840	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed Corner 865	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 1200 mm 840 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R

## Product family datasheet

Product description	Colors & materials			Temperatures & operating conditions	Capabilities	Certificates & standards		Country specific categorizations
	Body material	Product color	Cover material	Ambient temperature range	Type of installation	Protection class	Type of protection	Order reference
LEDTOUCH Skyline Recessed 1200 mm 865 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 600 mm 840 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed 600 mm 865 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed Corner 840 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R
LEDTOUCH Skyline Recessed Corner 865 DALI	steel	signal white (RAL 9003)	PMMA	-20...+40 °C	recessed	insulation class I (protective earthing)	IP20	LDTH SKYLINE R

## Product family datasheet

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.